

Required basic technical characteristics of the used crane for the ŠKRLJEVO terminal

- Hydraulic mobile port crane on pneumatic (rubber) wheels
- Power supply unit - diesel
- Load capacity 60 - 65 tons
- Minimum working radius 40 meters
- Reach/load table (curve) - meter/ton
- Minimum rotation speed 1.35 rpm
- Hook lift height above the rails min. 25-26 meters
- Lowering the hook under the rails min. 15 meters
- The hook must be able to rotate 360 ° and lock
- An electric cable must be routed to the hook for connecting hydraulic devices (grab, spreader...)
- The maximum wind speed at which the crane can work is 20 m/s - 72 km/h
- Cabin with air conditioning (heating-cooling)
- LED work lights on the branch, girder, tower and crane cabine
- Color video surveillance, zoom camera on the crane and monitor in the tower cabin
- Catalog of parts, operating instructions, services and detailed diagram of the crane in Croatian and English in written form and on CD or USB stick
- Detailed scheme of electrical installation and hydraulics
- Remote crane control
- Software (diagnostics) for determining faults
- Warranty period of 24 months or 4000 working hours and spare parts included in price during the warranty period
- Training of crane operators, electricians, electronics and mechanics in duration min. 5-7 days
- Time of production, delivery, installation and commissioning

- Register certificate BV, LR, GLS, DNV
- Maximum age of used crane up to 5 years and with a maximum of 5000 operating hours

The offer must include delivery of the crane to the terminal, installation, commissioning and handover.