

BASIC TECHNICAL CONDITIONS OF ELECTRO FORKLIFT

RATED CAPACITY 4.000 kg CONTAINER VERSION FOR

ŠKRLJEVO TERMINAL – Pcs.2

1.	Drive	Electric
2.	Battery voltage (V)	min. 80
3.	Battery capacity (Ah)	min. 900
4.	Battery charger (fast)	Yes
5.	Double battery	Option
6.	Operator type	Seated
7.	Rated capacity (kg)	4.000
8.	Load centre distance (mm)	600 or more
9.	Type of tyres	Superelastic
10.	Number of tyres	4 (6)
11.	Mast	Triplex
12.	Free lift (mm)	min. 1.200
13.	Lift (mm)	min. 3.800
14.	Overall width (mm)	max. 1.450
15.	Height above protected roof (cab) (mm)	max. 2.250
16.	Forks dimensions (mm)	60 x 150 x 1.200
17.	Double pallet handler with integrated forks positioner (3T429C-560-2160mm)	Yes
18.	Integrated lateral displacement	Yes
19.	Protective fence on fork carriage	Yes
20.	Lights (front/rear) and roto – lamp	Yes
21.	View mirror (exterior + interior)	Yes
22.	Siren	Yes
23.	Acoustic signal on reverse driving	Yes
24.	Cabin with air conditioning or heating / cooling	Yes
25.	Display monitor	Appearances due to certain truck conditions by message/graphic symbol. Appearances of an error code
26.	Lifting eyes (raising/lowering on the ship and trailer)	Yes

27.	Display in driver`s cab should provide information in Croatian	Yes
28.	Manual instructions, servicing, supply schemes	Yes
29.	Catalogue of spare parts	Yes
30.	Spare parts for maintenance provided in service instructions during the warranty period – included in price	Yes
31.	Software (diagnostics) for determining faults with the main code	Yes
32.	Warranty	min. 2 years / 4.000 working hours
33.	Battery life at max. load	min. 8 h

Lights and roto – lamp must be within maximum width/high of the forklift

Lifting eyes for raising/lowering on the ship/trailer should not exceed the height of the forklift

The protective fence on the fork carriage must not exceed the width of the forklift