

BASIC TECHNICAL FORKLIFT CONDITIONS LOAD 6.000 kg FOR ŠKRLJEVO TERMINAL**Pcs.1**

1.	Power unit	Diesel
2.	Operation	Seat
3.	Load capacity (kg)	6.000
4.	Load centre (mm)	600 or more
5.	Service weight (kg)	10.000 - 11.000
6.	Tire model	Standard pneumatic, heavy duty
7.	Number of tires	6
8.	Free lift (mm)	min. 150
9.	Lift (mm)	min. 4.800
10.	Overall width (mm)	max. 2.300
11.	Overall length with forks (mm)	max. 5.000
12.	Overall length without forks (mm)	max. 3.800
13.	Hight of overhead guard – cabin (mm)	max. 3.500
14.	Fork dimensions (mm)	60 x 130 x 1.200
15.	Integrated lateral displacement	Yes
16.	Protective fence on fork carriage	Yes
17.	Protective grille on the forklift cabin	Yes
18.	Noise level at operator`s ear (dB(A))	70 – 80
19.	Lights (front/rear)[1] and roto – lamp	Yes
20.	Horn	Yes
21.	Acoustic signal on reverse driving	Yes
22.	Cabine with air condition	Yes
23.	Display monitor	Showing working hours/measuring motor temperature/transmission temperature/oil pressure/cooling water level etc...
24.	Lifting eyes (raising/lowering on the ship and trailer)[2]	Yes
25.	Display in the driver`s cabine should provide information in Croatian	Yes
26.	Manual instructions, servicing, hydraulic and power supply schemes	Yes
27.	Catalog of spare parts	Yes
28.	Software (diagnostics) for determining faults with the main code	Yes
29.	Two sets of spare filters	Yes
30.	Spare parts for maintenance provided in service instructions during the warranty period – included in price	Yes

31.	Warranty	min. 2 years / 4.000 working hours
-----	----------	------------------------------------

[1] Lights and roto – lamp must be within maximum width/high of the forklift

[2] Lifting eyes for raising/lowering on the ship/trailer should not exceed the height of the forklift

(3) There has to be a protection fence on the fork carriers

REGULATIONS:

1. Declaration of EU conformity
2. Sounds regulations acc. Last valid Regulations, outside cabine
3. Sounds regulation acc. Last valid Regulations, inside cabine
4. Emission regulations TIER acc. Last valid Regulations
5. EN - regulation rear view including main hydraulic connection, prepared for hydraulic sideshift and work positioning

WORKING CONDITIONS:

1. Engine and emissions in accordance with regulations in EU (Diesel - Deutz), water - cooled
2. Transmission hydrostatic, automatic engine speed control
3. Cabine built according to the latest ergonomical standard; noise < 75 dB; warmth isolated; hydraulically tiltable cabine security according to EURO regulation. Visibility at all angles. Bulletproof glass roof
4. Cabine design - optimised legroom, ergonomic pedal system, high capacity wipers with washers for windscreen, roof and rear windows, folding wind mirror, rearview mirror, heating and defrosting with multi stage fan, air conditioning, sun visor roof screen; Work console - easy to use and easy to understand (controls, switches and indicators)
5. Cabine positioned in center
6. Lights: two lights on the mast front, two lights on the frond fenders, two backup lights (switch on automaticly), brake lights, cabine and instrument lights
7. Forklift designated for timber and other general cargo for manipulations on ships and warehouses; for irregular land surfaces - crossing over rail and crane tracks. Working in open air and over the influence of salinity and dust.
8. Additional equipment - spare parts for maintenance in service instructions during the warranty period (min. 24 months or 4.000 operation hours) included in price.
- 9.- Repair tool set

