

BASIC TECHNICAL FORKLIFT CONDITIONS LOAD 6.000 kg
FOR TERMINAL BRŠICA - PCS. 2

1.	Power unit	Diesel
2.	Operation	Seat
3.	Load capacity (kg)	6.000
4.	Load centre (mm)	600
5.	Service weight (kg)	10.000 - 11.000
6.	Tire model	Standard pneumatic, heavy duty
7.	Number of tires	6 (4/2)
8.	Crane (boom)	Duplex
9.	Free lift (mm)	min. 110
10.	Lift (mm)	min. 4.800
11.	Overall width (mm)	max. 2.300
12.	Type of transmission	Hydrostatic/Hydraulic
13.	Overall length without forks (mm)	max. 3.600
14.	Hight of overhead guard – cabin (mm)	max. 3.600
15.	Fork dimensions (mm)	60 x 130 x 1.200
16.	Noise level at operator`s ear (dB(A))	70 – 80
17.	Lights (front/rear)[1] and roto – lamp	Yes
18.	Horn	Yes
19.	Acoustic signal on reverse driving	Yes
20.	Cabine with air condition	Yes
21.	Display in the driver`s cabine should provide information in Croatian	Showing working hours/measuring motor temperature/transmission temperature/oil pressure/cooling water level etc...
22.	Lifting eyes (raising/lowering on the ship and trailer)[2]	Yes
23.	Integrated side shift	Yes
24.	Cabine positioned in center	Yes
25.	Manual instructions, servicing, hydraulic and power supply schemes	Yes
26.	Forklift spare parts catalog	Yes
27.	Warranty period	24 manths or 4000 operating hours
28.	Spare parts for maintenance provided in service instructions during the warranty period – included in price	Yes
29.	Diagnostic device for detection and service cancellation	Yes
30.	Hydraulic and electro diagram	Yes
31.	Training and getting to know drivers and mechanics with forklift	Yes
32.	Ce certificate	Yes
33.	Two sets of spare filters	yes
34.	Set of forklift repair tools	Yes

[1] Lights and roto – lamp must be within maximum width/high of the forklift

[2] Lifting eyes for raising/lowering on the ship/trailer should not exceed the height of the forklift

(3)There has to be a protection fence on the fork carriers