

**BASIC TECHNICAL FORKLIFT CONDITIONS LOAD 6.000 kg  
FOR TERMINAL RIJEKA - PCS. 4**

1.	Power unit	Diesel
2.	Operation	Seat
3.	Load capacity (kg)	6.000
4.	Load centre (mm)	600
5.	Service weight (kg)	10.000 - 11.000
6.	Tire model	Standard pneumatic, heavy duty
7.	Number of tires	6 (4/2)
8.	Crane (boom)	Duplex
9.	Free lift (mm)	min. 110
10.	Lift (mm)	min. 4.800
11.	Overall width (mm)	max. 2.300
12.	Type of transmission	Hydrostatic/Hydraulic
13.	Overall length without forks (mm)	max. 3.600
14.	Hight of overhead guard – cabin (mm)	max. 3.600
15.	Fork dimensions (mm)	60 x 130 x 1.200
16.	Protective grille on the fork carriage	Yes
17.	Noise level at operator`s ear (dB(A))	70 – 80
18.	Lights - front/rear and roto lamp must be within maximum width/high of the forklift	Yes
19.	Horn	Yes
20.	Acoustic signal on reverse driving	Yes
21.	Cabine with air condition	Yes
22.	Display in the driver`s cabine should provide information in Croatian or English	Showing working hours/measuring motor temperature/transmission temperature/oil pressure/cooling water level etc...
23.	Lifting eyes (raising/lowering on the ship and trailer)[2]	Yes
24.	Integrated side shift	Yes
25.	Cabine positioned in center	Yes
26.	Manual instructions, servicing, hydraulic and power supply schemes	Yes
27.	Forklift spare parts catalog	Yes
28.	Warranty period	24 manths or 4000 operating hours
29.	Spare parts for maintenance provided in service instructions during the warranty period – included in price	Yes
30.	Diagnostic device for detection and service cancellation	Yes
31.	Hydraulic and electro diagram	Yes
32.	Training and getting to know drivers and mechanics with forklift	Yes
33.	Ce certificate	Yes
34.	Two sets of spare filters	yes
35.	Protective grille on the roof of a forklift	Yes
36.	Mandrel for Coils - length 1000mm, diameter (fi) 180mm - pictures attached	Yes
37.	Set of forklift repair tools	Yes

**The offer must include the price of the machine with delivery to the Rijeka terminal, assembly and handover.**